

Silicone Rubber Perimeter Seals

IS1005si, IS1006si, IS1007si, IS1008si



Durable, bulb-type silicone compression seals, which can be easily kerf mounted into the rebates of timber door and window frames. These provide ideal smoke and acoustic seals for single action doors. These silicone compression seals can be fitted into a nominal 3mm wide kerf of sufficient depth.

Gap size

- IS1005si: Required Door Clearance 3-5mm
- IS1006si: Required Door Clearance 3-6mm
- IS1007si: Required Door Clearance 4-7mm
- IS1008si: Required Door Clearance 5-8mm

Standard lengths

- 50 metre coils

Standard colours

- Black
- Grey
- (Dark brown available to special order)

Approval/s

- Conforms with NCC Specification C3.4 smoke sealing requirements
- Medium temperature smoke leakage approvals to AS1530 Part 7 available on proprietary door assemblies
- Acoustically tested in accordance with AS1191, ISO140.3 and ISO10140-2



Right: IS1006si: silicone compression seals utilised on stiles of solid timber bi-fold doors. (Shown with IS5111si sweep seals fitted top and bottom).




IS1005si



IS1006si



IS1007si



IS1008si



Right: IS1007si: silicone compression seals shown fitted to a timber door frame rebate.

