



Length:

**Description of contents**

- Aluminium drip guard
- Flexible cover strip
- Stainless steel fixing
- Screws and plugs
- Fitting instruction

**Tools required for installation**

- Tape measure
- Pencil or marker
- Saw (power or hand)
- Power drill
- 4mm drill bit
- 6mm masonry drill

**Other Integrity™ Architectural Seals include:**

- Door Perimeter Seals
- Door Bottom Seals
- Automatic Door Bottom Seals
- Threshold Plates
- Brush Seals
- Magnetic Seals

Contact your nearest Kilargo office for further details.

**Installation detail:  
Rain drip guard**

*It is not necessary to remove the door from its hinges. However ensure the proposed position of the guard does not interfere with the operating arc of the door.*

- 
- Step 1** Remove the drip guard from the packaging and measure the door frame width.
- 
- Step 2** Guard width should be the same as the overall frame width (if fixing directly to the frame) or add 100mm to frame width to provide a 50mm overhang on either side of the door frame (if fixing to the wall).
- 
- Step 3** Remove flexible cover strip. Mark the guard with a pencil to the desired length and cut through using a saw.
- 
- Step 4** Using a power drill with a 4mm drill bit, create fixing holes in the guard at the required positions.
- 
- Step 5** Position the guard centrally above the door and mark out hole centres.
- 
- Step 6** Using a power drill with a 6mm masonry bit, create fixing holes in required position. Insert supplied fixing plugs. (Metal door jambs, if mortar filled, will require a clearance hole before drilling with a masonry bit. If unfilled, drill pilot holes and screw fix with stainless self tappers supplied).
- 
- Step 7** Apply a bead of water resistant sealant along the back face and fix the guard in position using supplied stainless steel screws.
- 
- Step 8** Refit the flexible cover strip to hide screw heads and trim to length.
- 

*Note: For effective operation, the IS9010 drip guard requires a minimum of 38mm overhang either side of the door.*

**Note**

Recommendations as to methods for use of materials and construction details are based on the experience and knowledge of Kilargo and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Kilargo reserves the right to make alterations or delete any installation detail without prior notice.

**Important**

Ensure that the installation of this product does not impede the opening or closing of the door.

