

IS4050s

IS4055s

IS4060s

IS4065s

Length:

### Description of contents

- Stainless steel threshold
- Stainless steel screws and plugs
- Fitting instruction

### Tools required for installation

- Tape measure
- Pencil or marker
- Saw (power)
- Power drill
- 6mm masonry drill
- Sealant (optional)
- 4.5mm Drill bit
- Countersink

### Other Integrity™ Architectural Seals include:

- Door Perimeter Seals
- Door Bottom Seals
- Automatic Door Bottom Seals
- Threshold Plates
- Brush Seals
- Magnetic Seals

Contact your nearest Kilargo office for further details.

## Installation detail: Stainless steel threshold plates

- Step 1** Remove the plate from the packaging and measure the door width, between jambs or door stops to determine the plate length required.
- Step 2** Measure the threshold plate and mark the desired length (and profile if cutting around door stop) with a pencil.
- Step 3** Position the plate on the door sill in required location.
- Step 4** Using a power drill with 4.5mm drill bit, create fixing holes in the plate at required positions. Countersink to ensure flush screw heads.
- Step 5** With the threshold plate in position, mark hole centres on the floor. Using masonry drill, create fixing holes. Clean away dust and insert supplied plastic plugs.
- Step 6** Screw fix the threshold into place using stainless steel screws and plastic plugs supplied.  
*Note: For exterior applications, where threshold plate meets the door stop, sealant should be applied to prevent water ingress.*

*Note: For effective door operation, the IS4055s and IS4060s threshold plates require a minimum of 8mm clearance, and the IS4050s and IS4065s threshold plates require a minimum of 15mm clearance between the door and the floor.*

### Important

Ensure that the installation of this product does not impede the opening or closing of the door.

### Note

Recommendations as to methods for use of materials and construction details are based on the experience and knowledge of Kilargo and are given in good faith as a general guide and service to designers, contractors and manufacturers. Kilargo reserves the right to make alterations or delete any installation detail without prior notice.

