

Kilargo IS4035 Threshold Plate

[Click here to view on website](#)




SKU	Length
LO-IS4035-1000CA	1000mm
LO-IS4035-2250CA	2250mm

DESCRIPTION

This heavy duty, threshold plate is used in conjunction with other Kilargo door bottom seals to help prevent rain infiltration, draught and smoke penetration.

These threshold plates have a durable, anodised finish and are supplied with PVC bedding feet to help eliminate vibration, noise and moisture ingress.



Standard Lengths

- 1000mm
- 2250mm
- Also available in: 250mm increments from 1000mm to 3250mm (Special Order Only)

Standard Finishes

- Silver anodised aluminium

Fixing

- Stainless Steel fixing screws and plugs are supplied
- Alternatively, fasten with builder's adhesive for concealed fixing

Approvals

- Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1

SPECIFICATION

Material	Aluminium
AS1428 Compliant	No
Includes Fixing Screws	Yes
Fire tested, check with manufacturer for further details.	Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
Depth	100mm
Finish	Silver anodised aluminium
Gradient	NA
Height	11mm
Warranty	2 years from date of sale

CATEGORIES

Door Seals / Threshold Plates & Ramps

Contact

Customer Service: 1800 555 600
Locksmith Services: 1800 555 700
Email: online@accesshardware.com.au
Website: www.accesshardware.com.au

Disclaimer

The specifications on our website are often provided to us by our manufacturers, provided as guidance only. While Access ensures it deals with reputable manufacturers, it cannot verify the accuracy of every claim made by them about their products as manufacturers often reserve the right to make changes without notice. To the extent permitted by law, We are not liable in respect of any claims made on this website in respect of any specification or claim by a manufacturer for its product.