

Kilargo IS4120 Threshold Plate


[Click here to view on website](#)



SKU	Length
LO-IS4120-1000CA	1000mm
LO-IS4120-2250CA	2250mm
LO-IS4120-2500CA	2500mm

DESCRIPTION

The IS4120 threshold plates is used in conjunction with other Kilargo door bottom seals to help prevent rain, draughts, and smoke penetration. Their low profile ensures compliance with the "access for people with disability" requirements, particularly for wheelchair traffic.



Standard Lengths

- 1000mm
- 2250mm
- 2500mm
- Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Standard Finishes

- Silver anodised aluminium

Fixing

- Stainless Steel fixing screws and plugs are supplied
- Alternatively, fasten with builder's adhesive for concealed fixing

Approvals

- Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
- Complies with AS1428 Part 1 (Design for access and mobility)
- Conforms to NCC D2.15 & D3.3 (Access for people with disabilities)

SPECIFICATION

Material	Aluminium
AS1428 Compliant	Yes
Includes Fixing Screws	Yes
Fire tested, check with manufacturer for further details.	Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
Finish	Silver anodised aluminium
Gradient	NA
Depth	40mm
Height	5mm
Warranty	2 years from date of sale

CATEGORIES

Door Seals / Threshold Plates & Ramps

Contact

Customer Service: 1800 555 600
Locksmith Services: 1800 555 700
Email: online@accesshardware.com.au
Website: www.accesshardware.com.au

Disclaimer

The specifications on our website are often provided to us by our manufacturers, provided as guidance only. While Access ensures it deals with reputable manufacturers, it cannot verify the accuracy of every claim made by them about their products as manufacturers often reserve the right to make changes without notice. To the extent permitted by law, We are not liable in respect of any claims made on this website in respect of any specification or claim by a manufacturer for its product.