## **B Round Rose Door Furniture - Specifications**

#### FEATURES

Size Fixing	54mm diameter x 10mm thick. Concealed 38mm-41mm horizontal bolt through fixing.	Material	Manufactured from grade 304 stainless steel for ultimate durability.
Standard Finishes	SSS, PSS.		
Door Thickness	32-50mm doors.	Spindle	7.6mm Standard


#### ORDERING CODES

B01	Complete Set	
B02	Half Set	
B03	Blank Rose	
B04	Privacy Set	
B06	Concealed Turn Snib Round	
B07	Visible Turn Snib Oval	
B08	Cylinder Escutcheon	
B09	Emergency Release	
B09I	Emergency Release Indicating	
B10	Euro Escutcheon	
Privacy Set Indicating B09I/B07/12907 bolt through with screw on cap		
Privacy Set Indicating B09I/B06/12907 bolt through with screw on cap		
Privacy Set Indicating B09I/B06D/12907 bolt through with screw on cap		
10	10	
	BO2 BO3 BO4 BO6 BO7 BO8 BO9 BO9 BO9 B10 cy Set brough cy Set brough	

### Finishes

Satin Stainless Steel	SSS
Polished Stainless Steel	PSS

Door Handing



Manufactured to suit Australian mortice locks and latches. Order 8mm spindle to suit European locks.

#### Ordering Example

### BO166SSS

Finish(SSS, PSS)

Lever Design (63, 65, 66, 72, 80)

Rose Design (B01-B10)



B Round Rose

**B** Round Escutcheons



## B Round Rose Door Furniture - Lever Options

LEVER 30

LEVER 35





LEVER 31



LEVER 38

LEVER 68













## B Round Rose Door Furniture - Dimensional Drawings






LEVER 38










LEVER 32





## B Round Rose Door Furniture - Lever Options

LEVER 63

LEVER 72





LEVER 65

LEVER 66






LEVER 50









### B Round Rose Door Furniture - Dimensional Drawings







LEVER 66




LEVER 54











## B Round Rose Door Furniture - Lever Options


LEVER 51


LEVER 55





## B Round Rose Door Furniture - Dimensional Drawings







#### Novas Maintenance of Stainless Steel

Retaining the attractive finish of stainless steel is easy with a few simple maintenance steps. When maintained properly, stainless steel will retain its visual appeal and structural integrity in wide range of applications and environments.

Novas Stainless Steel products are designed to be durable, low maintenance, highly resistant to corrosion and easily maintained resulting in a high quality, pleasing appearance.

### **Cleaning Stainless Steel**

Stainless Steel is best cleaned using a mild detergent and a soft cloth, after washing, rinse in clean, cold water and wipe the surface dry with a soft absorbent cloth. Drying afterwards ensures there no streaky marks on the surface.

### Retaining Surface Integrity

Stainless looks best if its cleaned regularly and correctly which prevents stubborn stains building up. The level of cleaning and maintenance depends primarily on its environment where the product is situated.

### 1.Sea Side

When Stainless Steel is in a coastal environment, tea staining of surface can occur. Tea staining is discoloration of the surface of stainless steel by corrosion. It is a cosmetic issue that does not affect the structural integrity or the lifetime of the material. Discoloration or a tea staining effect most commonly occurs within 5 kilometers of the coast and becomes progressively worse closer to the water. Regular washing also removes deposits (such as salt) that can cause corrosion. In these instances, it is recommended that cleaning is performed fortnightly.

### 2.Interior

Dirt, grease and fingerprints can accumulate from many sources. These can be removed by routine cleaning using a mild detergent and a soft cloth. After washing, rinse in clean, cold water and wipe the surface dry with a soft absorbent cloth. Drying afterwards ensures there are no streaky marks left on the surface. If a mild detergent or dishwashing liquid doesn't shift unsightly stains/finger-marks, then wipe over with glass cleaner on a soft cloth. You can also use a small amount of alcohol, methylated spirits, acetone or mineral turpentine. Then rinse with clean water and dry. You can give longer protection to high traffic areas by lightly rubbing with olive oil or baby oil followed by a polish and shine using a soft cloth.

#### 3.Exterior

In most exterior environments normal rain washing is sufficient, but in more polluted or coastal regions the surfaces will require regular washing to retain its pristine condition. (see above in Sea Side for more details) Discoloration or a tea staining effect most commonly occurs within 5 kilometres of the coast and becomes progressively worse closer to the water. For rust or tougher stains apply a cream cleanser with a soft damp cloth, rib gently then rinse with clean cold water. Dry with an absorbent soft cloth.

### Surface Protection

It is important to know that Stainless Steel can be scratched so it is important to be aware that harsh abrasives, steel wool or plastics scourers must NEVER be used. Cloths used to rub over the stainless steel must be free of grit or chemicals and always avoid vigorous rubbing.

Strong minerals acids such as hydrochloric, hydrofluoric acid or bleach should never be permitted to come in contact with stainless steel. If this should happen, the solution must be washed off immediately with plenty of water.

Never use oil based commercial cleaners as the residual oil film can result in an iridescent colour on Stainless Steel.

Environment	Maintenance Schedule			
Seafront / Chlorinated Pool	Fortnightly			
Coastal (within 5km of coast)Monthly				
Industrial and Urban	Every 3-6 months			
Suburban Rural	Annually or as required			
Internal	As required to maintain appearance			

Please note: Unless regular maintenance of the Stainless Steel surface occurs to the appropriate schedule, the Novas Guarantee will be rendered void.