


IS9070

Fitting Instructions: Finger Guard Seal



Length:

Description of contents

- Decorative cover strip (1)
- Aluminium carrier (2)
- Pre-slotted holes (3)
- Flexible gasket (4)
- Bag of screws
- Fitting instructions

Tools required for installation

- Tape Measure
- Saw (Power or Hand)
- Screw Driver
- Drill (Power or Hand)
- 2.5mm Drill Bit
- Knife
- Pencil or marker

Other Kilargo Architectural Seals include:

- Door Perimeter Seals
- Door Bottom Seals
- Automatic Door Bottom Seals
- Threshold Plates
- Brush Seals
- Magnetic Seals

Contact your nearest Kilargo office for further details.

Installation detail: Finger guard seal

It is not necessary to remove the door from its hinges unless otherwise specified.

- Step 1** Remove the seal from the packaging and measure the existing jambs (sides) of the door frame to determine the seal length required.
- Step 2** Remove the decorative cover strip from the aluminium carriers.
- Step 3** Pull back flexible gasket and cut the aluminium carriers to the lengths required.
- Step 4** Cut the decorative cover strips to the lengths required.
- Step 5** Slide flexible gasket back into position and cut to required length.
- Step 6** Position the aluminium carriers to the door stop and side of the door and mark out the slotted hole locations with a pencil. (Refer to the diagram for the correct orientation of the product).
- Step 7** Lightly screw-fix each length through the slotted holes with the screws supplied. (Fixing holes are pre-slotted to enable the seal to be accurately adjusted as required).
- Step 8** Ensure that the Finger Guard profile extends right to the bottom of the door leaf but does not drag on the floor. Check for correct operation as the door is opened and closed.
- Step 9** Tighten the screws and replace the decorative cover strip.

We recommend the IS9070 be fitted with a Kilargo IS9050 Finger Guard Seal on the hinge side of the door.

Note: If you require a door bottom seal, only use a product that can be fully mortised. For example, IS8010si or IS8100si.

Note



Recommendations as to methods for use of materials and construction details are based on the experience and knowledge of Kilargo and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Kilargo reserves the right to make alterations or delete any installation detail without prior notice.

**** Note:** when fitting to hinged doors, the IS9070 seal has a maximum opening limitation of 110°. Kilargo does not recommend the installation of the IS9070 on aluminium door frame systems.

Important

Ensure that the installation of this product does not impede the opening or closing of the door. It is



Literature Code: IS9070 06/17

15 Wentworth Place, Banyo Qld 4014
T 1300 858 010 F +61 7 3861 9266 E sales@kilargo.com.au www.kilargo.com.au