




Kilargo IS3021si Door Bottom Seal 19mm - Clear Anodised Aluminium

LO-IS3021

PRODUCT OPTIONS

Door Seal Length: 1000mm 2250mm



DESCRIPTION

The IS3021si (finned) seal can be fitted to door bottoms or meeting stiles of single and double action doors. They can also be utilised for door bottoms on roller type doors.

This seal can provide effective containment against medium and ambient temperature smoke, sound, dust, light, weather and vermin.

Gap Size

Min. 20mm / max. 24mm

Standard Lengths

1000mm

2250mm

Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Standard Colours

Silver anodised aluminium with grey silicone gasket (black silicone gasket also available to special order)

Fixing

Timber fixing screws are supplied with detailed fitting instructions
Fixing holes are pre-drilled to allow the seals to be positioned accurately

Approvals

Conforms to BCA Specification C3.4 for smoke doors (when fitted to compliant door leaves)

SPECIFICATION

MPN IS3021SI
Brand Kilargo
Product Height 24.75mm
Product Thickness 35mm

Product Finish or Colour Clear Anodised (CA)

Product Material Aluminium
Includes Fixing Screws Yes
Fire Tested No



Kilargo IS3021si Door Bottom Seal 19mm - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 29/4/24

Acoustic Rated to AS1191 and ISO140.3 Yes
Suitable for Smoke Doors
Yes

Suitable for Door Type Timber Doors

Contains Intumescent MaterialNoSeal Can Be InstalledConcealedBrush / Gasket Length19mmGasket / Seal ColourGrey

Gasket Material Silicon Impregnated

Min Door Gap20mmMax Door Gap24mmProduct Warranty2 Years

ADDITIONAL IMAGES





Print Date: 29/4/24