




# Kilargo IS4020 Threshold Plate 6mm - Clear Anodised Aluminium

LO-IS4020

## PRODUCT OPTIONS

Length: 1000mm  
2250mm  
2500mm



## DESCRIPTION

These heavy duty, low profile threshold plates are used in conjunction with other Kilargo door bottom seals to help prevent rain infiltration, draught and smoke penetration. Their 6mm low profile design ensures compliance with the 'access for people with disability' requirements, AS1428/1 and BCA D3, particularly for wheelchair traffic.

These threshold plates have a durable, anodised finish and are supplied with PVC bedding pads to help eliminate vibration, noise and moisture ingress.

### Standard Lengths

1000mm  
2250mm  
Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

### Standard Finishes

Silver anodised aluminium

### Fixing

Stainless Steel fixing screws and plugs are supplied  
Alternatively, fasten with builder's adhesive for concealed fixing

### Approvals

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1  
Certifications GYYI.R26629, GVWZ.R26629, GVWZ7.R26629  
Complies with AS1428 Part 1 (Design for access and mobility)  
Conforms to NCC D2.15 & D3.3 (Access for people with disabilities)

## SPECIFICATION

MPN	IS4020
Brand	Kilargo
Product Width	125mm
Product Height	6mm
Product Finish or Colour	Clear Anodised (CA)
Product Material	Aluminium
Includes Fixing Screws	Yes



### Kilargo IS4020 Threshold Plate 6mm - Clear Anodised Aluminium

Scan to view online and for additional product information, or call us on **1800 555 600**.

Print Date: 27/4/24

<b>AS1428.1 Compliant</b>	Yes
<b>Fire Tested</b>	Yes
<b>Acoustic Rated to AS1191 and ISO140.3</b>	No
<b>Min Door Gap</b>	6mm
<b>Product Warranty</b>	2 Years



**Kilargo IS4020 Threshold Plate 6mm - Clear Anodised Aluminium**  
*Scan to view online and for additional product information , or call us on **1800 555 600**.*

*Print Date: 27/4/24*