




Kilargo IS4060s Threshold Plate 6mm - Stainless Steel

LO-IS4060

PRODUCT OPTIONS

Length: 1000mm
2250mm



DESCRIPTION

These stainless steel threshold plates are used in conjunction with other Kilargo door bottom seals to help prevent rain infiltration, draught and smoke penetration.

These durable Grade 304 stainless steel threshold plates have a No. 4 brush finish and are impervious to most chemicals, solvents, cleaning fluids and disinfectants. They are suitable for external environments.

The IS4055S has a low profile design (6mm height), complying with the 'access for people with disability' requirements of AS1428/1 and NCC D2.15 & D3.3.

Standard Lengths

1000mm
2250mm
Also available in: 250mm increments from 1000mm to 3250mm (Special Order Only)

Standard Finishes

Grade 304 Stainless Steel with No. 4 Brush Finish

Fixing

Appropriate stainless steel fixing screws and plugs supplied

Approvals

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1

SPECIFICATION

MPN	IS4060
Brand	Kilargo
Product Width	125mm
Product Height	6mm
Product Finish or Colour	Satin Stainless Steel (SSS)
Product Material	304 Stainless Steel
Includes Fixing Screws	Yes
AS1428.1 Compliant	Yes
Fire Tested	Yes



Kilargo IS4060s Threshold Plate 6mm - Stainless Steel

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 28/4/24

Acoustic Rated to AS1191 and ISO140.3 No
Product Warranty 2 Years



Kilargo IS4060s Threshold Plate 6mm - Stainless Steel
*Scan to view online and for additional product information , or call us on **1800 555 600**.*

Print Date: 28/4/24