




Kilargo IS4070 Threshold Plate 14mm - Clear Anodised Aluminium

LO-IS4070

PRODUCT OPTIONS

Length: 1000mm
2250mm
2500mm



DESCRIPTION

This threshold ramp is for use in buildings where wheelchairs and trolleys are used or to compensate for uneven floors. The rate of incline ensures compliance with the 'access for people with disability' requirement, particularly for wheelchair traffic.

These threshold ramps have a durable, anodised finish and are supplied with PVC bedding pads to help eliminate vibration, noise and moisture ingress.

Gradient

1:8

Standard Lengths

1000mm
2250mm
2500mm

Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Standard Finishes

Silver anodised aluminium

Fixing

Stainless steel fixing screws and plugs supplied

These extrusions can be positioned back-to-back to provide a two-way threshold ramp

Approvals

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1

Complies with AS1428 Part 1 (Design for access and mobility)

Conforms to NCC D2.15 & D3.3 (Access for people with disabilities)

SPECIFICATION

MPN	IS4070
Brand	Kilargo
Product Width	100mm
Product Height	14mm
Product Finish or Colour	Clear Anodised (CA)



Kilargo IS4070 Threshold Plate 14mm - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 26/4/24

Product Material	Aluminium
Includes Fixing Screws	Yes
AS1428.1 Compliant	Yes
Fire Tested	Yes
Acoustic Rated to AS1191 and ISO140.3	No
Product Warranty	2 Years



Kilargo IS4070 Threshold Plate 14mm - Clear Anodised Aluminium
*Scan to view online and for additional product information , or call us on **1800 555 600**.*

Print Date: 26/4/24