




# Kilargo IS4075 Threshold Plate 14mm - Clear Anodised Aluminium

LO-IS4075

## PRODUCT OPTIONS

Length: 1000mm  
2250mm  
2500mm



## DESCRIPTION

This threshold ramp is for use in buildings where wheelchairs and trolleys are used or to compensate for uneven floors. The rate of incline ensures compliance with the 'access for people with disability' requirement, particularly for wheelchair traffic.

These threshold ramps have a durable, anodised finish and are supplied with PVC bedding pads to help eliminate vibration, noise and moisture ingress.

### Gradient

1:12

### Standard Lengths

1000mm  
2250mm  
2500mm

Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

### Standard Finishes

Silver anodised aluminium

### Fixing

Stainless steel fixing screws and plugs supplied

These extrusions can be positioned back-to-back to provide a two-way threshold ramp

### Approvals

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1

Complies with AS1428 Part 1 (Design for access and mobility)

Conforms to NCC D2.15 & D3.3 (Access for people with disabilities)

## SPECIFICATION

MPN	IS4075
Brand	Kilargo
Product Width	150mm
Product Height	14mm
Product Finish or Colour	Clear Anodised (CA)



### Kilargo IS4075 Threshold Plate 14mm - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 23/4/24

<b>Product Material</b>	Aluminium
<b>Includes Fixing Screws</b>	Yes
<b>AS1428.1 Compliant</b>	Yes
<b>Fire Tested</b>	Yes
<b>Acoustic Rated to AS1191 and ISO140.3</b>	No
<b>Product Warranty</b>	2 Years



**Kilargo IS4075 Threshold Plate 14mm - Clear Anodised Aluminium**  
*Scan to view online and for additional product information , or call us on **1800 555 600**.*

*Print Date: 23/4/24*