




# Kilargo IS4120 Threshold Plate 5mm - Clear Anodised Aluminium

LO-IS4120

## **PRODUCT OPTIONS**

Length: 1000mm 2250mm 2500mm



# DESCRIPTION

The IS4120 threshold plates is used in conjunction with other Kilargo door bottom seals to help prevent rain, draughts, and smoke penetration. Their low profile ensures compliance with the 'access for people with disability' requirements, particularly for wheelchair traffic.

#### **Standard Lengths**

1000mm 2250mm 2500mm Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

#### **Standard Finishes**

Silver anodised aluminium

#### Fixing

Stainless Steel fixing screws and plugs are supplied Alternatively, fasten with builder's adhesive for concealed fixing

#### Approvals

. . . . .

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1 Complies with AS1428 Part 1 (Design for access and mobility) Conforms to NCC D2.15 & D3.3 (Access for people with disabilities)

### **SPECIFICATION**

MPN	IS4120
Brand	Kilargo
Product Width	40mm
Product Height	5mm
Product Warranty	2 Years
<b>Product Finish or Colour</b>	Clear Anodised (CA)
Product Material	Aluminium
Includes Fixing Screws	Yes
AS1428.1 Compliant	Yes
Fire Tested	Yes



Kilargo IS4120 Threshold Plate 5mm - Clear Anodised Aluminium Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 30/4/24

Acoustic Rated to AS1191 and ISO140.3 No



**Kilargo IS4120 Threshold Plate 5mm - Clear Anodised Aluminium** Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 30/4/24