




Kilargo IS4130 Threshold Plate 4mm - Clear Anodised Aluminium

LO-IS4130

PRODUCT OPTIONS

Length: 1000mm
2250mm
2500mm



DESCRIPTION

The IS4130 threshold plates is used in conjunction with other Kilargo door bottom seals to help prevent rain, draughts, and smoke penetration. Their low profile ensures compliance with the 'access for people with disability' requirements, particularly for wheelchair traffic.

Standard Lengths

1000mm
2250mm
2500mm
Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Standard Finishes

Silver anodised aluminium

Fixing

Stainless Steel fixing screws and plugs are supplied
Alternatively, fasten with builder's adhesive for concealed fixing

Approvals

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
Complies with AS1428 Part 1 (Design for access and mobility)
Conforms to NCC D2.15 & D3.3 (Access for people with disabilities)

SPECIFICATION

MPN	IS4130
Brand	Kilargo
Product Width	40mm
Product Height	4mm
Product Finish or Colour	Clear Anodised (CA)
Product Material	Aluminium
Includes Fixing Screws	Yes
AS1428.1 Compliant	Yes
Fire Tested	Yes
Acoustic Rated to AS1191 and ISO140.3	No



Kilargo IS4130 Threshold Plate 4mm - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 26/4/24



Kilargo IS4130 Threshold Plate 4mm - Clear Anodised Aluminium
*Scan to view online and for additional product information , or call us on **1800 555 600**.*

Print Date: 26/4/24