




Kilargo IS4220si Threshold Plate 6mm - Clear Anodised Aluminium

LO-IS4220SI

PRODUCT OPTIONS

Length: 1000mm
2250mm



DESCRIPTION

The IS4220si threshold plate is suitable for outward opening doors to prevent rain, draughts, light and noise penetration. The high performance silicone rubber compression seal, combined with the vinyl bedding pads, help provide an effective acoustic barrier.

May be used with a panic type exit device
(supplied to suit by others).

Standard Lengths

1000mm
2250mm
Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Standard Finishes

Silver anodised aluminium with grey silicone gasket

Fixing

Stainless Steel fixing screws and plugs are supplied
Alternatively, fasten with builder's adhesive for concealed fixing

Approvals

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
Certifications GVI.R26629, GVWZ.R26629, GVWZ7.R26629
Medium temperature smoke leakage approvals to AS1530 Part 7 available on proprietary door assemblies
Acoustically tested in accordance with AS1191, ISO140.3 and ISO10140-2

SPECIFICATION

MPN	IS220SI
Brand	Kilargo
Product Width	125mm
Product Height	14mm
Product Finish or Colour	Clear Anodised (CA)
Product Material	Aluminium
Includes Fixing Screws	Yes
AS1428.1 Compliant	No



Kilargo IS4220si Threshold Plate 6mm - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 9/4/24

Fire Tested	Yes
Acoustic Rated to AS1191 and ISO140.3	Yes
Product Warranty	2 Years

ADDITIONAL IMAGES



Kilargo IS4220si Threshold Plate 6mm - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 9/4/24