



# Kilargo IS7020si Perimeter Seal - Clear Anodised Aluminium



### **PRODUCT OPTIONS**


Door Seal Length: 1000mm

2250mm 2500mm

Single Door Set (1x1000mm, 2x2100mm)

Double Door Set (3x2100mm)

Long Single Door Set (1x1000mm, 2x2750mm)
Long Double Door Set (1x2000mm, 2x2750mm)



#### **DESCRIPTION**

The IS7020si is aesthetically designed, a slim-line compression type perimeter seal for installation around the head and jambs of single swing doors. It is proven to be effective acoustic, smoke, light, dust and weather seals. The aluminium carrier is pre-drilled and slotted for adjustable retrofit installation. The easy to install, 'snap-on', anodised aluminium (or coloured PVC) cover plates provide concealed fixings.

#### **Gap Size**

Min. 0mm / Max. 6mm

## Standard Lengths

1000mm

2250mm

2500mm

1 x 1000mm, 2 x 2100mm

1 x 1000mm, 2 x 2750mm

3 x 2100mm

1 x 2100mm, 2 x 2750mm

Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

## **Standard Finishes**

Silver anodised aluminium with grey silicone gasket (Black silicone gaskets also available upon request)

### **Fixing**

When fixing IS7020si to rebated frames of single doors, specify a long back set door latch

## **Approvals**

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1 Medium temperature smoke leakage approvals to AS1530 Part 7 available on proprietary door assemblies Acoustically tested in accordance with AS1191, IS0140.3 and ISO10140-2



## **SPECIFICATION**

MPN IS7020SI
Brand Kilargo
Product Width 33mm
Product Height 7.5mm
Product Warranty 2 Years

Product Finish or Colour Clear Anodised (CA)

Product Material Aluminium

Includes Fixing ScrewsYesFire TestedYesAcoustic Rated to AS1191 and ISO140.3YesSuitable for Smoke DoorsYes

**Suitable for Door Type** Timber Doors, Aluminium Doors

Contains Intumescent MaterialNoSeal Can Be InstalledSurface FixGasket / Seal ColourGreyGasket MaterialSiliconMin Door GapOmmMax Door Gap6mmSelf AdhesiveNo

# **ADDITIONAL IMAGES**



