




# Kilargo IS7060si Meeting Style - Astragal Seal - Clear Anodised Aluminium

LO-IS7060SI

### **PRODUCT OPTIONS**

Door Seal Length: 2250mm

2500mm 3000mm



## **DESCRIPTION**

An astragal seal used with either plain or rebated meeting stiles on single swing, double doors (where only one door leaf is active). It provides an excellent acoustic, smoke, light, dust and weather seal. The thin fixing leg allows this seal to be face fixed to the door (no rebating required). This leg can also be checked to make way for locks and latches.

#### **Gap Size**

Min. 2.5mm / Max. 10mm

### **Standard Lengths**

2250mm

2500mm

3000mm

Also available in: 250mm increments from 2000mm to 3500mm (Special Order Only)

#### **Standard Finishes**

Silver anodised aluminium with grey silicone gasket

(black anodised aluminium with black silicone gasket to special order)

#### **Fixing**

A door sequence selector should be considered unless one leaf is intended to be fixed

## **Approvals**

Medium temperature smoke leakage approvals to AS1530 Part 7 available on proprietary door assemblies. Conforms with NCC Specification C3.4 smoke sealing requirements. Acoustically tested in accordance with AS1191, IS0140.3 and ISO10140-2.

# **SPECIFICATION**

MPN IS7060SI
Brand Kilargo
Product Width 25mm
Product Thickness 20mm

Product Finish or Colour Clear Anodised (CA)

**Product Material** Aluminium



Kilargo IS7060si Meeting Style - Astragal Seal - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 26/4/24

Includes Fixing ScrewsYesFire TestedNoAcoustic Rated to AS1191 and ISO140.3YesSuitable for Smoke DoorsYes

**Suitable for Door Type** Timber Doors

Contains Intumescent Material No

Seal Can Be Installed
Gasket / Seal Colour
Gasket Material
Min Door Gap
Max Door Gap
Self Adhesive
Product Warranty
Surface Fix
Grey
Silicon
2.5mm
10mm
No

# **ADDITIONAL IMAGES**







Print Date: 26/4/24