



# Kilargo IS7090si Perimeter Seal - Clear Anodised Aluminium

LO-IS7090SI

#### **PRODUCT OPTIONS**


Door Seal Length: 1000mm

2250mm 2500mm

Single Door Set (1x1000mm, 2x2100mm)

Double Door Set (3x2100mm)

Long Single Door Set (1x1000mm, 2x2750mm)
Long Double Door Set (1x2000mm, 2x2750mm)



#### **DESCRIPTION**

IS7090si self-adjusting and adjustable (spring-loaded) perimeter seal is designed for high performance acoustic applications. This seal can be fitted to the head and jambs of door frame perimeters in lieu of door stops, where frames are non fire-rated. It's unique spring loaded mechanism, automatically self-adjusts to cater for movement or uneven doors. It is also mechanically adjustable to ensure the desired seal is maintained. Durable polypropylene fins are incorporated within the gasket housing to provide additional smoke and acoustic sealing properties. An aesthetic, anodised aluminium tamper-proof cover plate simply clips onto the main carrier to conceal fixings.

#### **Gap Size**

Min. 0mm / Max. 8mm

#### **Standard Lengths**

1000mm

2250mm

2500mm

Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Single Door Set (1 x 1000mm, 2 x 2100mm)

Long Single Door Set (1 x 1000mm, 2 x 2750mm)

Double Door Set (3 x 2100mm)

Long Double Door Set (1 x 2100mm, 2 x 2750mm)

#### **Standard Finishes**

Silver anodised aluminium with grey silicone gasket

### **Fixing**

When fixing the IS7090si seal to rebated frames of single doors, specify a long back set door latch

## **Approvals**

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1

Medium temperature smoke leakage approvals to AS1530 Part 7 available on proprietary door assemblies

Acoustically tested in accordance with AS1191, IS0140.3 and ISO10140-2

Durability tests demonstrating over 100,000 open and close cycles



## **SPECIFICATION**

MPN IS7090SI
Brand Kilargo
Product Width 47mm
Product Height 20mm

Product Finish or Colour Clear Anodised (CA)


Product MaterialAluminiumIncludes Fixing ScrewsYesFire TestedYesAcoustic Rated to AS1191 and ISO140.3YesSuitable for Smoke DoorsYes

**Suitable for Door Type**Timber Doors, Aluminium Doors

Contains Intumescent MaterialNoSeal Can Be InstalledSurface FixGasket / Seal ColourGreyGasket MaterialSiliconMin Door Gap0mmMax Door Gap8mm

Max Door Gap8mmSelf AdhesiveNoProduct Warranty2 Years

## **ADDITIONAL IMAGES**





Print Date: 25/4/24