




Kilargo IS3100si Door Bottom Seal 24mm - Clear Anodised Aluminium

LO-IS3100SI

PRODUCT OPTIONS

Door Seal Length: 1000mm 2250mm



DESCRIPTION

The IS3100si set incorporates an IS3070si door bottom seal plus an IS4100si threshold plate.

The IS3070si weather resistant door bottom seal can be fitted without removing the door, and can be used with alternative threshold plates. This seal provides effective containment against cold smoke, sound, dust, light, insects and weather. The aesthetic cover strip ensures there is no visible screw line.

Gap Size

Min. 21mm / Max. 24mm

Standard Lengths

1000mm 2250mm

Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Standard Colours

Silver anodised aluminium carrier with grey silicone gasket and cover strip (Black silicone gasket and cover strip also available upon request)

Fixing

Fixing screws are supplied with detailed fitting instructions Fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately

Approvals

Conforms to NCC Specification C3.4 smoke sealing requirements Acoustically tested in accordance with AS1191, IS0140.3 and ISO10140-2

SPECIFICATION

MPN Brand Product Height Product Thickness Product Finish or Colour Product Material IS3100SI Kilargo 37mm 35mm Clear Anodised (CA) Aluminium



Kilargo IS3100si Door Bottom Seal 24mm - Clear Anodised Aluminium Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 26/4/24

Includes Fixing Screws	Yes
Fire Tested	Yes
Acoustic Rated to AS1191 and ISO140.3	Yes
Suitable for Smoke Doors	Yes
Suitable for Door Type	Timber Doors
Contains Intumescent Material	No
Seal Can Be Installed	Surface Fix
Brush / Gasket Length	14mm
Gasket / Seal Colour	Grey
Gasket Material	Silicon Impregnated
Min Door Gap	12mm
Max Door Gap	20mm
Product Warranty	2 Years

ADDITIONAL IMAGES





Kilargo IS3100si Door Bottom Seal 24mm - Clear Anodised Aluminium Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 26/4/24