




Raven RP38 Automatic Door Bottom Seal - Clear Anodised Aluminium

RP38

PRODUCT OPTIONS

Door Seal Length: 450mm
610mm
920mm
1070mm
1220mm
1500mm



DESCRIPTION

A heavy duty, automatic door bottom seal that is spring loaded to lift clear of the floor when the door is opened. It is self levelling and reversible for left and right handed operation. Acoustically designed, it features an EPDM foam gasket for acoustic door applications and doubles as a kick plate when semi-morticed. Operated automatically by pressure against the door jamb or stop on its adjustable brass strike.

Location: Face mounted or semi-morticed into bottom of single and double butt hinged doors. For semi-mortice minimum door thickness of 50mm for rebated meeting stiles and 40mm for plain meeting stiles is required. The RP38 can also be face mounted to the bottom of metal doors.

Min/Max Gap: 3mm to 13mm.

Finish: Satin clear (silver) anodised aluminium (15micron) or paint at extra cost.

Fixing: Screw fix. Colour matched escutcheon plates and zinc plated, cross recess head S.T. screws supplied.

Seal: RP338. Black EPDM sponge (SE).

Sizes: 1500mm, 1220mm, 1070mm, 920mm, 610mm, 450mm to 300mm(min). Seals cut back to exact size.

Approvals

Acoustic AUS/NZ: NCC Spec. F5.5.

UK/EU: Approved Document E. Rated to BS EN ISO 717.1.

Fire & Smoke AUS/NZ: NCC Spec. C3.4. AS1530.4 & AS/NZS 1905.1. NZ BC Compliance Doc. C/AS1 6.19.2 & App. C6.1.1.

UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

FRL & FRR-/240/30 and FD240. Fire Approved

Energy NCC Pt. 3.12.3.3 & J3.4.

Design for Access and Mobility High efficiency mechanism to assist with the closing force requirements detailed in AS1428.1.

Durability Tested to over 1,000,000 operating cycles without failure.

Patented.

SPECIFICATION

MPN	A38C
Brand	Raven
Product Height	70mm
Product Warranty	2 Years
Product Thickness	26mm
Product Finish or Colour	Clear Anodised (CA)




Raven RP38 Automatic Door Bottom Seal - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 2/5/24

Product Material	Aluminium
Includes Fixing Screws	Yes
Fire Tested	Yes
Suitable for Smoke Doors	Yes
Acoustic Rated to AS1191 and ISO140.3	Yes
Suitable for Door Type	Timber Doors
Bush Fire Attack Level	Fire Zone
Contains Intumescent Material	No
Seal Can Be Installed	Surface Fix / Semi-Rebated
Gasket / Seal Colour	Black
Gasket Material	Silicon Impregnated
Min Door Gap	3mm
Max Door Gap	13mm

ADDITIONAL IMAGES



Raven RP38 Automatic Door Bottom Seal - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 2/5/24