


Raven RP51Si Door Bottom Sweep Seal 20mm - Clear Anodised Aluminium

RP51SI

PRODUCT OPTIONS

Door Seal Length: 1000mm 1250mm 1500mm 2000mm 3000mm



DESCRIPTION

A heavy duty silicon rubber sweep seal for the bottom of outward opening doors. RP51Si has slotted fixing holes for adjustment with a push-in cover strip for concealed fixing.

The RP51Si is ideal for use in conjunction with Raven threshold plates.

Location: Bottom of single and double, outward opening, butt hinged doors, tilt up doors or can be used as an astragal seal. Min/Max Gap: 5mm to 20mm (user determined).

Finish: Satin clear (silver), bronze anodised aluminium (15micron) or paint at extra cost.

Fixing: Concealed screw fix. Zinc plated, cross recess head S.T. screws and cover strip supplied. Fixing holes are pre-slotted. Seal: RP351Si. Grey silicon Rubber (SE).

Sizes: Available in stock lengths.

Approvals

Fire & Smoke AUS/NZ: NCC Spec. C3.4. AS1530.4 & AS/NZS 1905.1. NZ BC Compliance Doc. C/AS1 6.19.2 & App. C6.1.1. UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1). FRL & FRR-/120/30 and FD120.Fire Approved Gasket flammability index 1 when tested to AS1530.2. Energy NCC Pt. 3.12.3.3 & J3.4.

SPECIFICATION