




Raven RP117Si Threshold Plate Seal - 15mm - Clear Anodised Aluminium

RP117SI

PRODUCT OPTIONS

Product Length: 1000mm 2000mm



DESCRIPTION

The RP117Si is a weather proof threshold plate seal suited to outward opening butt hinged doors. It is ideal for use with a panic type exit device (by others).

For acoustic applications the void under the threshold should be filled with sound foam or other suitable material (by others).

The RP67 drip strip should be considered for above the doorway if there is no eave.

Ideal for use in conjunction with the Raven RP118Si perimeter seal and Raven astragals.

Location: Door sill of outward opening doors. (butt hinges recommended).

Min/Max Gap: Compression 0mm to 2mm.

Finish: Satin clear (silver) anodised aluminium (25micron).

Fixing: Screw fix or builders adhesive for concealed fixing (user determined). Zinc plated, cross recess head CSK S.T. screws supplied.

Seal: RP308Si. Grey silicon rubber (SE). Sizes: Available in stock lengths.

Approvals

UL Cert. GVYI.R37913

Access & Mobility NZ: NZ BC Compliance Doc. D1/AS1 1.3.2.

UK/EU: Approved Document M. Acoustic AUS/NZ: NCC Spec. F5.5.

UK/EU: Approved Document E. Rated to BS EN ISO 717.1.

Fire & Smoke AUS/NZ: NCC Spec. C3.4. NZ BC Compliance Doc. C/AS1 6.19.2 & App. C6.1.1.

UK/EU: Approved Document B. FRL & FRR-/240/30. Fire Approved

Gasket flammability index 1 when tested to AS1530.2.

Fire Approved when used with a BAL rated door bottom seal in accordance with AS 3959.

Energy NCC Pt. 3.12.3.3 & J3.4.

SPECIFICATION

MPN A111SIC
Brand Raven
Product Width 100mm
Product Height 15mm

Product Finish or Colour Clear Anodised (CA)

Product Material Aluminium



Raven RP117Si Threshold Plate Seal - 15mm - Clear Anodised Aluminium

Scan to view online and for additional product information, or call us on **1800 555 600**.

Print Date: 28/4/24

Includes Fixing ScrewsYesAS1428.1 CompliantNoFire TestedYesAcoustic Rated to AS1191 and ISO140.3YesProduct Warranty2 Years

ADDITIONAL IMAGES

