



Raven RP13 Threshold Plate 5mm - Clear Anodised Aluminium

25

RP13

PRODUCT OPTIONS

Product Length: 1000mm 2000mm

3000mm

DESCRIPTION

A low profile threshold plate that is ideal for use in conjunction with Raven door bottom seals to prevent rain, draughts, noise and smoke infiltration.

Location: Door sill.

Finish: Satin clear (silver) or bronze anodised aluminium (25micron).

Fixing: Screw fix or builders adhesive for concealed fixing (user determined). Colour matched zinc plated, cross recess head CSK S.T. screws supplied.

Sizes: Available in stock lengths.

Approvals UL Cert. GVYI.R37913 Access & Mobility AUS/NZ: NCC D2.15 & D3.3, AS1428.1 and NZ BC Compliance Doc. D1/AS11.3.2. UK/EU: Approved Document M. Fire AUS/NZ: NCC Spec. C3.4. AS1530.4 & AS/NZS 1905.1. NZ BC Compliance Doc. C/AS1 6.19.2(a) & App. C6.1.1. UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1). FRL & FRR-/240/30. Fire Approved Fire Approved when used with a BAL rated door bottom seal in accordance with AS 3959.

SPECIFICATION

| MPN | A13C |
|---------------------------------------|---------------------|
| Brand | Raven |
| Product Width | 25mm |
| Product Height | 5mm |
| Product Finish or Colour | Clear Anodised (CA) |
| Product Material | Aluminium |
| Includes Fixing Screws | Yes |
| AS1428.1 Compliant | Yes |
| Fire Tested | Yes |
| Acoustic Rated to AS1191 and ISO140.3 | No |
| Product Warranty | 2 Years |
| | |

ADDITIONAL IMAGES





