



Raven RP58 Brush Seal 75mm - Clear Anodised Aluminium

RP58

PRODUCT OPTIONS

Door Seal Length: 1000mm

2000mm 3000mm



DESCRIPTION

Nylon brush strip seals with aluminium carriers that are ideal where larger gaps are encountered. They can be fitted to lintels of roll-up doors to help prevent the ingress of birds and wind blown embers in bushfire prone areas.

Note: Roll-up doors must have a fairly consistent gap when the door operates to avoid excessive flexing of the seal.

Location: Bottom of single, double, revolving or sliding doors and double acting pivot doors. Lintels of roll-up garage doors.

Min/Max Gap: 50mm to 75mm (user determined).

Finish: Satin clear (silver) anodised aluminium (15micron) or paint at extra cost.

Fixing: Self adhesive or can be screw fixed. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: Black fine, dense, UV stabilised nylon filaments.

Sizes: Available in stock lengths.

Approvals

Energy NCC Pt. 3.12.3.3 & J3.4.

Fire Approved when used on a garage in accordance with AS 3959.

SPECIFICATION

MPN A58C
Brand Raven
Product Height 95mm
Product Thickness 7mm

Product Finish or Colour Clear Anodised (CA)

Product MaterialAluminiumIncludes Fixing ScrewsYesFire TestedNoAcoustic Rated to AS1191 and ISO140.3NoSuitable for Smoke DoorsNo

Suitable for Door Type Timber Doors, Aluminium Doors

Bush Fire Attack LevelBAL <29</th>Contains Intumescent MaterialNoSeal Can Be InstalledSurface FixBrush / Gasket Length75mmGasket MaterialNylon Brush



Print Date: 25/4/24

Min Door Gap30mmMax Door Gap50mmSelf AdhesiveYesProduct Warranty2 Years

ADDITIONAL IMAGES





Print Date: 25/4/24