




# Raven RP3 Automatic Door Bottom Seal - Clear Anodised Aluminium

RP3

### **PRODUCT OPTIONS**

Door Seal Length: 920mm 1220mm



#### **DESCRIPTION**

A cam activated, lifting action, automatic door bottom seal. It is quick and easy to install without cutting or removing the door and uses concealed fasteners. This DIY product has been granted an Australian Design Award. Ideal for residential and light commercial applications such as motels and retirement villages.

Can be used in conjunction with Raven threshold plates.

Location: Bottom of single inward opening butt hinged doors.

Min/Max Gap: 1mm to 16mm.

Finish: Satin clear (silver), bronze or bright gold anodised aluminium (15µm).

Fixing: Screw fix. Zinc plated, cross recess head S.T. screws supplied. Fixing holes are pre-slotted.

Seal:RP303. Black EPDM or TPE.

Sizes: 915mm and 1220mm maximum (between door stops).

**Approvals** 

Fire Gasket flammability index < 5 when tested to AS1530.2.

Energy NCC Pt. 3.12.3.3 & J3.4.

Durability Tested to over 1,000,000 operating cycles without failure.

Patented.

## **SPECIFICATION**

MPN R3C
Brand Raven
Product Height 27mm

**Product Finish or Colour** Clear Anodised (CA)

Product MaterialAluminiumIncludes Fixing ScrewsYesFire TestedNo



Raven RP3 Automatic Door Bottom Seal - Clear Anodised Aluminium

Scan to view online and for additional product information, or call us on **1800 555 600**.

Print Date: 26/4/24

Suitable for Smoke Doors Yes
Acoustic Rated to AS1191 and ISO140.3 No

**Suitable for Door Type** Timber Doors, Aluminium Doors

**Bush Fire Attack Level** BAL<40 **Contains Intumescent Material** No Seal Can Be Installed Surface Fix Gasket / Seal Colour Black Rubber TPE **Gasket Material** Min Door Gap 3mm **Max Door Gap** 16mm **Product Warranty** 2 Years

## **ADDITIONAL IMAGES**





Print Date: 26/4/24