




Kilargo IS7130si Perimeter Seal - Clear Anodised Aluminium

LO-IS7130

PRODUCT OPTIONS

Door Seal Length: 1000mm

2250mm 2500mm



DESCRIPTION

The IS7130 is an effective acoustic seal suitable for fitting to door stops of sufficient depth, around the head and jambs of single swing doors. It has two silicone compression gaskets providing excellent acoustic and air leakage containment. It can also be rebated into meeting stiles and door bottoms as a sweep-action type seal.

Gap Size

Min. 6mm / Max. 8mm (when recessed)
Allow 12mm to 13mm when surface-mounted

Standard Lengths

1000mm

2250mm

2500mm

Also available in: 250mm increments from 1000mm to 5000mm (Special Order Only)

Aluminium

Standard Finishes

Silver anodised aluminium with grey silicone gaskets (Black silicone gaskets also available upon request)

Approvals

Acoustically tested in accordance with AS1191, IS0140.3 and ISO10140-2

SPECIFICATION

MPN IS7130SI
Brand Kilargo
Product Width 19mm
Product Height 13.5mm

Product Finish or Colour Clear Anodised (CA)

Includes Fixing ScrewsYesFire TestedNoAcoustic Rated to AS1191 and ISO140.3YesSuitable for Smoke DoorsYes



Product Material

Suitable for Door TypeTimber Doors, Aluminium Doors

Contains Intumescent Material No

Seal Can Be Installed
Gasket / Seal Colour
Gasket Material
Min Door Gap
Max Door Gap
Self Adhesive
Product Warranty
Surface Fix
Grey
Grey
6mm
8mm
8mm
2 Years

ADDITIONAL IMAGES





Print Date: 20/4/24