




# Kilargo IS8010si-KG Intumescent Automatic Door Bottom Seal - Clear Anodised Aluminium

LO-8010SI-KG

## PRODUCT OPTIONS

Door Seal Length: 600mm  
820mm  
920mm  
1070mm  
1220mm



## DESCRIPTION

### Kilargo IS8010si-KG Intumescent Automatic Door Bottom Seal

A medium-duty, concealed automatic door bottom seal incorporating intumescent within the silicone gasket for hot smoke applications, which is mortised into the bottom edge of single-action doors. It operates automatically by a spring-loaded mechanism which lifts the seal clear of the floor as soon as the door is opened.

Mounted into a 35mm deep x 15mm wide machined groove, the seal is screwfixed back into the door stiles via stainless steel end plates, holding the seal in place. The seal operates automatically by pressure against the door jamb on its adjustable strike button. The seal contains a high-efficiency mechanism to assist with the closing force requirements detailed in AS1428/1 (Design for Access and Mobility).

### Gap Size

Min. 3mm / Max. 15mm

### Available Lengths

600mm  
820mm  
920mm  
1070mm  
1220mm

### IS8010si Maximum allowable cut-back sizes

600mm seal cuts to 380mm  
820mm seal cuts to 600mm  
920mm seal cuts to 820mm  
1070mm seal cuts to 920mm  
1220mm seal cuts to 1070mm

(\*Seals can be cut on site for exact dimension).

### Standard Colours

Silver anodised aluminium with stainless steel end plates, grey silicone gasket.  
(Black silicone gasket also available upon request.)



**Kilargo IS8010si-KG Intumescent Automatic Door Bottom Seal - Clear Anodised Aluminium**

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 26/4/24

## Approvals

Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1  
Certifications GVYI.R26629, GVWZ.R26629, GVWZ7.R26629  
Medium temperature smoke leakage tests to AS1530 Part 7 available on proprietary door assemblies  
Conforms to BCA Specification C3.4 for smoke sealing requirements  
Acoustic ratings to AS1191, ISO140.3 and ISO10140-2  
Durability tests demonstrating over 1,000,000 open and close cycles

## SPECIFICATION

<b>MPN</b>	IS8010SI-KG
<b>Brand</b>	Kilargo
<b>Product Height</b>	35mm
<b>Product Thickness</b>	14mm
<b>Product Finish or Colour</b>	Clear Anodised (CA)
<b>Product Material</b>	Aluminium
<b>Includes Fixing Screws</b>	Yes
<b>Fire Tested</b>	Yes
<b>Suitable for Smoke Doors</b>	Yes
<b>Acoustic Rated to AS1191 and ISO140.3</b>	Yes
<b>Suitable for Door Type</b>	Timber Doors
<b>Contains Intumescent Material</b>	Yes
<b>Seal Can Be Installed</b>	Concealed
<b>Gasket / Seal Colour</b>	Grey
<b>Gasket Material</b>	Silicon Impregnated
<b>Min Door Thickness</b>	30mm
<b>Min Door Gap</b>	3mm
<b>Max Door Gap</b>	15mm
<b>Product Warranty</b>	2 Years



**Kilargo IS8010si-KG Intumescent Automatic Door Bottom Seal - Clear Anodised Aluminium**  
Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 26/4/24