



Raven RP520 Silicon Weather Strip

RP520


PRODUCT OPTIONS

Roll Length: 24 Meters

100 Meters

Product Finish or Colour: Black (BLK)

Brown (BRN) White (WHT)



DESCRIPTION

A compression seal, made from silicon. Raven silicon has a high resistance to permanent set (memory). It will not absorb water and is resistant to ozone and ultra-violet light deterioration.

Location: Aluminium, PVC or timber door and window frame grooves where dimensions suit.

Compression: 1mm to 3mm. Finish: White, brown or black.

Fixing: Push-in locking fit into a 3.5mm x 5mm deep kerf groove.

Sizes: 100m, 24m.

Approvals

Acoustic AUS/NZ: NCC Spec. F5.5.

UK/EU: Approved Document E. Rated to BS EN ISO 717.1.

Weather AUS/NZ: NCC various sections. AS2047, AS4055, AS4420 Pt. 0 to 5 & AS/NZS 1170.

UK/EU: Approved Document L1 & L2. Tests above are similar to BS 5368 & BS 7386.

Energy NCC Pt. 3.12.3.3 & J3.4.

SPECIFICATION

MPNB520BrandRavenProduct Height8mmProduct Thickness13mmProduct MaterialSiliconIncludes Fixing ScrewsNoFire TestedNoAcoustic Rated to AS1191 and ISO140.3YesSuitable for Smoke DoorsYes

Suitable for Door Type Timber Doors, PVC, Aluminium Doors

Bush Fire Attack LevelBAL <29</th>Contains Intumescent MaterialNoSeal Can Be InstalledRebatedGasket MaterialSiliconMin Door Gap1mmMax Door Gap3mm



Raven RP520 Silicon Weather Strip

Scan to view online and for additional product information, or call us on **1800 555 600**.

Print Date: 27/4/24

