



Raven RP610 TPE Weather Strip

RP610


PRODUCT OPTIONS

Roll Length: 24 Meters

100 Meters

Product Finish or Colour: Black (BLK)

Brown (BRN) White (WHT)



DESCRIPTION

A compression seal, made from co-extruded flame retardant TPE rubber.

Location: Aluminium, PVC or timber door and window frame grooves where dimensions suit.

Compression: 1mm to 2mm. Finish: White, brown or black.

Fixing: Push in locking fit into a 3.5mm x 5mm deep kerf groove.

Sizes: 100m, 24m.

Approvals

Fire Flammability index less than or equal to 5 when tested to AS1530.3.

Weather AUS/NZ: NCC various sections. AS2047, AS4055, AS4420 Pt. 0 to 5 & AS/NZS 1170.

UK/EU: Approved Document L1 & L2. Tests above are similar to BS 5368 & BS 7386.

Energy NCC Pt. 3.12.3.3 & J3.4.

SPECIFICATION

MPN B610 **Brand** Raven **Product Height** 5mm **Product Warranty** 2 Years **Product Thickness** 10mm **Product Material** TPE **Includes Fixing Screws** No **Fire Tested** Acoustic Rated to AS1191 and ISO140.3 Yes **Suitable for Smoke Doors**

Suitable for Door Type Timber Doors, PVC, Aluminium Doors

Bush Fire Attack Level BAL<40
Contains Intumescent Material No
Seal Can Be Installed Rebated
Gasket Material TPE
Min Door Gap 1mm
Max Door Gap 2mm





Print Date: 2/5/24