



Raven RP530 Silicon Weather Strip

RP530


PRODUCT OPTIONS

Roll Length: 24 Meters

50 Meters

Finish or Colour*: Black (BLK)

Brown (BRN) White (WHT)



DESCRIPTION

A compression seal, made from silicon. Raven silicon has a high resistance to permanent set (memory). It will not absorb water and is resistant to ozone and ultra-violet light deterioration.

Location: Aluminium, PVC or timber door and window frame grooves where dimensions suit.

Compression: 1mm to 2mm. Finish: White, brown or black.

Fixing: Push-in locking fit into a 4mm x 6mm deep kerf groove.

Sizes: 50m, 24m.

Approvals

Acoustic AUS/NZ: NCC Spec. F5.5.

UK/EU: Approved Document E. Rated to BS EN ISO 717.1.

Weather AUS/NZ: NCC various sections. AS2047, AS4055, AS4420 Pt. 0 to 5 & AS/NZS 1170.

UK/EU: Approved Document L1 & L2. Tests above are similar to BS 5368 & BS 7386.

Energy NCC Pt. 3.12.3.3 & J3.4.

SPECIFICATION

MPN B530 Raven **Product Height** 6mm **Product Warranty** 2 Years **Product Thickness** 12mm **Product Material** Silicon **Includes Fixing Screws Fire Tested** No Acoustic Rated to AS1191 and ISO140.3 Yes **Suitable for Smoke Doors**

Suitable for Door Type Timber Doors, PVC, Aluminium Doors

Bush Fire Attack Level BAL <29
Contains Intumescent Material No
Seal Can Be Installed Rebated
Gasket Material Silicon
Min Door Gap 1mm



Raven RP530 Silicon Weather Strip

Scan to view online and for additional product information, or call us on **1800 555 600**.

Print Date: 10/5/25



Print Date: 10/5/25