



# FSH Slim Electromagnetic Lock - Monitored - Double -280kg

SKU FSH-FEM4300DM
MPNFEM4300DM



#### **DESCRIPTION**

The FSH FEM4300 Series of electromagnetic Locks come with a 5 year mechanical warranty and a hold strength of up to 280kg, so you have the peace-of-mind that entrances are secured to protect people and property.

Tested to Australian and New Zealand standards, including a 2-hour fire rating, these maglocks are Dual Voltage, 12/24VDC, and come in single or double (D) versions, either monitored (M) or non-monitored. Once powered off, the maglocks have no residual magnetism, which extends the life of the lock and door and gives a better user experience.

The monitored versions (M), include a red-green coloured LED indicator to quickly identify the door and lock status. Activated by a number of credential readers such as PIN pads, fob readers or other access control platforms, this range is ideal for most commercial applications.

#### **Features:**

Dual Voltage: 12 /24 VDC field selectable

Door and Lock Status Monitoring Sensor (DSS and LSS S with "M" Models)

Built-in varistor (MOV) surge protection

Red-Green bicolour LED on monitored version

No residual magnetism

5 year warranty

Fire Rated (up to 2-hour fire rated in accordance with AS 1905.1:2015)

#### **Technical Details:**

Holding strength: Up to 280kg.

Voltage/current: Dual Voltage 12/24VDC, 500mA/250mA.

Approvals: Up to 2-hour fire rated in accordance with AS1905.1:2015 (contact Allegion for more details). CE/C-Tick.

Monitoring: Red-green bicolour LED. Door Status Sensor (DSS).

Dimensions: Double door series magnet: 477mm (L) x 48mm (W) x 25mm (D). Double door series armature plate: 185mm (L) x 38mm (W) 12mm (D) x 2 pieces

### **SPECIFICATION**

MPN FEM4300DM

Brand FSH
Product Width 48mm
Product Length 477mm
Product Depth 25mm



Product MaterialAluminiumFire Rating2 HourFire TestedYesHolding Force280kgVoltage12 - 24V DCMonitoredYesProduct Warranty5 Years

## **ADDITIONAL IMAGES**



