



FSH Standard Electromagnetic Lock -Monitored - Double - 580kg

SKU FSH-FEM6600DM MPNFFM6600DM



DESCRIPTION

The FSH FEM6600 Series of electromagnetic locks come with a 5 year mechanical and electronic warranty and a hold strength of up to 580kg, so you have the peace-of- mind that entrances are secured to protect people and property.

Tested to Australian and New Zealand standards, including a 2-hour fire rating, these maglocks are Dual Voltage, 12/24VDC, and come in single or double (D) versions, either monitored (M) or non-monitored. Once powered off, the maglocks have no residual magnetism, which extends the life of the lock and door and gives a better user experience.

The monitored versions (M), include a red-green coloured LED indicator to quickly identify the door and lock status. Activated by a number of credential readers such as PIN pads, fob readers or other access control platforms, this range is ideal for most commercial applications.

Features:

Dual Voltage: 12 /24 VDC field selectable Door and Lock Status Monitoring Sensor (DSS and LSS S with "M" Models) Built-in varistor (MOV) surge protection Red-Green bicolour LED on monitored version No residual magnetism

5 year warranty

Fire Rated (up to 2-hour fire rated in accordance with AS 1905.1:2015)

Technical Details:

Holding strength: Up to 580kg.

Voltage/current: Dual Voltage 12/24VDC, 500mA/250mA.

Approvals: Up to 2-hour fire rated in accordance with AS1905.1:2015 (contact Allegion for more details). CE/C-Tick.

Monitoring: Red-green bicolour LED Lock Status Sensor (LSS) Door Status Sensor (DSS).

Dimensions: Double door series magnet: 535mm (L) x 3mm (W) x 40mm (D). Double door series armature plate: 190mm (L) x 61mm (W) x 16mm (D) x 2 pieces.

SPECIFICATION

MPN FEM6600DM

FSH **Brand Product Width** 73mm **Product Length** 535mm **Product Depth** 40mm



Product MaterialAluminiumFire Rating2 HourFire TestedYesHolding Force580kgVoltage12 - 24V DCMonitoredYesProduct Warranty5 Years

ADDITIONAL IMAGES



