



dormakaba ITS96 G96N EN 2-4 Concealed Door Closer - Silver

SKU DOITS96-2-4SIL

MPN 940000005635



DESCRIPTION

The dormakaba ITS 96 ushered in a new era for concealed door closer technology.

The door closer and slide channel are so compact that they can be installed into the door or door frame.

Suitable for timber, hollow metal and aluminium doors of 40mm minimum thickness and above and door widths to 1400mm by selection of the correct strength size.

Even once the closer has been installed, the speed control and strength can be adjusted without removal of the closer body from the door for user and installer convenience.

ITS96 G96N 2-4 is stocked and supplied by Access Hardware with standard G96N 31mm slide channel.

G96N20 (20mm) is an optional slide arm channel and should be priced and ordered differently to ITS96 G96N.

Size adjustable from size 2 to size 4

Concealed fitting in top of door

Cam action efficiency closer

Closing and latching speed adjustable

Minimum door thickness: 40mm

A perfect choice for hotels and apartments

Please check with us and your fire door manufacturer if considering use on fire doors as Australian fire approvals would have to be researched and approved before installation on any fire/hot smoke doors.

SPECIFICATION

MPN	940000005635
Brand	dormakaba
Product Warranty	10 Years Mechanical
Product Finish or Colour	Silver (SIL)
Product Material	Cast Iron
Includes Fixing Screws	Yes
AS1428.1 Compliant	No
Fire Tested	No
Spring Strength	Size 2-4 (EN2-4)
Back Check Valve	No
Hold Open Type	Optional
Adjustable Closing Speed	Yes



dormakaba ITS96 G96N EN 2-4 Concealed Door Closer - Silver

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 18/5/25

Delayed Action	No
Arm Type	Slide Rail Track Arm
Max Door Weight	130 Kilogram
Max Door Width	1100mm
Min Door Thickness	40mm
Suitable for	Commercial, Residential



dormakaba ITS96 G96N EN 2-4 Concealed Door Closer - Silver

Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 18/5/25