




# Kilargo IS1212 Flex-Wing Seal

LO-IS1212

## **PRODUCT OPTIONS**

Door Seal Length:	1000mm
	2100mm
	2400mm
	2700mm
	3000mm
	Single Door Set (1x1000mm, 2x2100mm)
	Double Door Set (3x2100mm)
	Long Single Door Set (1x1000mm, 2x2750mm)
	Long Double Door Set (1x2000mm, 2x2750mm)
Product Finish or Colour:	Black (BLK)
	White (WHT)



## DESCRIPTION

#### Description

These self-adhesive perimeter seals are fitted in the rebate of a door frame to contain smoke, sound, draughts, dust and light. Strategically located in the impact free zone, the seal adheres to the frame quickly and easily without having to remove the door.

The seal consists of a semi-rigid flame retardant PVC carrier combined with twin elastomeric sealing blades. An aggressive self-adhesive backing tape is situated on both sides of the carrier.

NB. To ensure proper adhesion, contact surfaces must be clean & any paint well-cured.

Gap Size

2-3mm

#### **Standard Colours**

Black White (Dark brown and grey available to special order)

#### Approvals

Fire tested to AS1530 Part 4 Medium temperature smoke leakage approvals to AS1530 Part 7 available on proprietary door assemblies Acoustic ratings to AS1191 and ISO140.3 Durability tests demonstrating over 100,000 open and close cycles

> IS1212 Kilargo 12mm 12mm Black (BLK)

### **SPECIFICATION**

MPN
Brand
Product Width
Product Height
Product Finish or Colour



Kilargo IS1212 Flex-Wing Seal Scan to view online and for additional product information , or call us on **1800 555 600**.

Print Date: 25/4/24

Product Material	Flame Retardant PVC
Fire Tested	Yes
Acoustic Rated to AS1191 and ISO140.3	Yes
Suitable for Smoke Doors	Yes
Suitable for Door Type	Timber Doors, Aluminium Doors
<b>Contains Intumescent Material</b>	No
Seal Can Be Installed	Surface Fix
Gasket Material	Flame Retardant PVC
Min Door Gap	2mm
Max Door Gap	3mm
Self Adhesive	Yes
Product Warranty	2 Years

## ADDITIONAL IMAGES

