McCallum A124 Aluminium Interfold Hinge - White - 100x34x3mm

SKU MCA124-WHT

MPNA124-WHT

DESCRIPTION

Hinge Type: Interfold Hinge
Material: High strength Aluminium Alloy T6 minimum tensile 254 mpa
Hinge Pin: 6mm Diameter Stainless Steel 304 grade.
Bushes: Flanged Nylon
Knuckle: Round Centre - Medium Duty
Endcaps: Aluminium Pressed Interference fit
Face Fix: Wrap-around face fixing to door & frame.
Hinge Positioning Locator: Yes
Maximum Weight Capacity: 20kg's – 3 Hinges
Minimum Door Thickness 35mm
Suitable for Aluminium & some Timber doors in Aluminium frames
As a guide doors: 2040 high x 820 up to 20kg – 3 hinges
Recommended that the minimum of 3 hinges be used with the top hinge located as high as possible.
Where door closers are or to be installed and or higher traffic doors a fourth hinge may be required
Fastening screws supplied:
Aluminium fixings - 10G x 13mm, Stainless Steel undercut countersunk self-tapping Phillips drive screw.
Face fixing to the door and frame.
Pop Rivets are NOT RECOMMENDED
Other finishes availiable to order:
A124SNA – Satin Natural Anodised
A124BLK – Black Powder Coat
A124SPC – Special Powder Coa

SPECIFICATION

MPN	A124-WHT
Brand	McCallum
Product Height	100mm
Product Width	34mm
Product Warranty	7 Years
Hinge Thickness	3.4mm
Hinge Size	100x34mm

Product Finish or Colour	White (WHT)
Product Material	Aluminium
Includes Fixing Screws	Yes
Fire Tested	No
Hinge Bearing Type	Flanged Nylon
Fixed / Loose Pin	Fixed
Suitable for	Commercial, Residential