



Raven RP60 Automatic Door Bottom Seal - 920mm - Clear Anodised Aluminium

SKU RP60-920CA

MPNR60C



DESCRIPTION

An adjustable, automatic door bottom seal which is spring loaded to lift clear of the floor when the door is opened. Operated automatically by pressure against the door stopon its adjusting screw and incorporates concealed fixings. The RP60 is self levelling and can be used in conjunction with Raven threshold plates such as the RP13 and RP82.

Location: Face mounted on the bottom of single and double butt hinged doors.

Min/Max Gap: 3mm to 15mm.

Finish: Satin clear (silver), bronze or bright gold anodised aluminium (15micron).

Fixing: Concealed screw fix. Zinc plated, cross recess head S.T. screws and cover strip supplied. Fixing holes are pre-slotted.

Seal:RP460. Black TPE.

Sizes: 915mm maximum (between door stops). Unit cuts back to 450mm (min).

Approvals

Fire AUS/NZ: NCC Spec. C3.4. AS1530.4 & AS/NZS 1905.1. NZ BC Compliance Doc. C/AS1 6.19.2 & App. C6.1.1.

UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

FRL & FRR-/240/30 and FD240. Fire Approved

Energy NCC Pt. 3.12.3.3 & J3.4.

Design for Access and Mobility High efficiency mechanism to assist with the closing force requirements detailed in AS1428.1.

Durability Tested to over 500,000 operating cycles without failure.

Patented.

SPECIFICATION

MPNR60CBrandRavenProduct Height41mmProduct Thickness15mmDoor Seal Length920mmProduct Length920mm

Product Finish or Colour Clear Anodised (CA)

Product Material Aluminium
Includes Fixing Screws Yes
Fire Tested Yes
Suitable for Smoke Doors Yes



Raven RP60 Automatic Door Bottom Seal - 920mm - Clear Anodised Aluminium

Scan to view online and for additional product information , or call us on 1800 555 600.

Print Date: 24/4/24

Acoustic Rated to AS1191 and ISO140.3 No

Suitable for Door Type **Timber Doors** Fire Zone **Bush Fire Attack Level Contains Intumescent Material** No Seal Can Be Installed Surface Fix **Gasket / Seal Colour** Black **Gasket Material** Rubber TPE Min Door Gap 3mm 15mm **Max Door Gap** 2 Years **Product Warranty**

ADDITIONAL IMAGES



